



**MATERIAL:** CONSTRUCTED FROM AN EXTRUDED POLYSTYRENE BASE, A FLEXIBLE CEMENTITIOUS BASECOAT AND A REVOLUTIONARY, POLYMER MODIFIED PLASTER FINISH.

**SMOOTH**

**NOTES:** THE LOOK AND FEEL OF A SEAMLESS PLASTER COVE. FABRICATED IN 8' LENGTHS, CUT AND MITRED TO FIT, THEN PRIMED AND PAINTED IN THE FIELD.

LUMAROC MOUNTS TO THE WALL USING SHEET ROCK SCREWS AND A GYPSUM BASED DRY WALL COMPOUND TO THE BACK AND TO THE JOINTS.

LIGHTING FIXTURES SHOULD BE MOUNTED TO THE WALL INDEPENDENT OF THE COVE FITTING.

LIGHT WEIGHT DESIGN.  
LUMAROC IS A STABLE LUMINAIRE FITTING THAT WILL NOT CRACK SHRINK OR SWELL.

## LUMAROC TRADITIONAL CAT # LRTR-8000-8000

SCALE: NONE	DATE: 03/13/2010	DRAWN BY: MJW	SHEET: 1 of 1
----------------	---------------------	------------------	------------------

## CLASSIC COVES

PO BOX 266 GARWOOD, NJ 07027  
Phone 908-344-1776 Fax: 908-345-6176  
[www.classiccoves.com](http://www.classiccoves.com)

SPACE PROVIDED FOR LIGHTING WILL ACCEPT T-5 & T-8 STRIP LIGHTS  
FIRE RATED - ASTME-84